

NPPB15EL

Designed for versatility across various environments, the **C-Series NPPB15EL** electric pallet truck delivers reliable performance for general applications. Whether in warehouses, distribution centers, or retail settings, this pallet truck's efficient load-bearing mechanisms enhance load transfer, ensuring smooth and stable operations.

Built for durability and efficiency, the **NPPB15EL** electric pallet truck seamlessly adapts to diverse operational needs. Whether handling short-distance shuttles or heavy transfers, it excels in performance and reliability.



Performance

- ▶ **Powerful motors** enable easy lifting of heavy loads.
- ▶ **Compact design** allows operators to manoeuvre within tight spaces.
- ▶ **Ergonomic control handler** provides effortless steering.
- ▶ **Rugged steer and load wheels** deliver smooth and quiet rolling with less resistance.
- ▶ **Quick 4.5km/h travel speed** can be achieved even with a maximum carrying load.



Long-Term Reliability

- ▶ **24V/20Ah Lithium-Ion Battery** provides longer usage life cycles and is designed to meet challenging tasks.
- ▶ **Easy battery exchange** allows the battery pack to be swapped out on the go for extended use.
- ▶ **Strong torsion-resistance chassis** for safe lifting of loads up to 1.5 tonne.
- ▶ **Emergency button** enables instant shutdown for safer operation.
- ▶ **Tested components** assure safety and reliability.

Service & Maintenance

- ▶ **Durable power-coated finish** protects the pallet truck from corrosion in the harshest environments.
- ▶ **Easy accessibility** to all key components for diagnosis, replacement, and lubrication.



NPPB15EL Specifications

Power		Electric
Max capacity	Q	1500kg
Load center distance	c	600mm
Load distance	x	950mm
Wheel base	y	1190mm
Weight		120kg
Tyre size (driving wheels)		210 x 70mm
Tyre size (loading wheels)		80 x 60mm
Track width, front, driving side	b10	/
Track width, front, loading side	b11	410mm
Lift height	h3	150mm
Height drawbar in driving position (min./max.)	h14	750/1190mm
Lowered height	h13	80mm
Overall length	l1	1540mm
Length to face of forks	l2	400mm
Overall width	b1	560mm
Fork dimensions	s/e/l	50 x 130 x 1150mm
Distance between fork-arms	b5	560
Ground clearance, center of wheelbase	m2	30mm
Aisle width for pallets 1000x1200 crossways	Ast	2145mm
Aisle width for pallets 800x1200 lengthways	Ast	2050mm
Turning radius	Wa	1330mm
Travel speed (laden/unladen)		4.5/5km/h
Lift speed (laden/unladen)		0.017/0.020m/s
Lowering speed (laden/unladen)		0.09/0.06m/s
Max. gradeability (laden/unladen)		6/16%
Max. battery size		200 x 100 x 350mm
Battery voltage		24v
Battery weight		7kg

